

PRODUCT DATA SHEET



POLYETHYLENE TAPE – RS778

DESCRIPTION

Our RS778 is a polyethylene backed pressure-sensitive adhesive tape with a synthetic rubber based adhesive. The adhesive is aggressive and will adhere well to a variety of surfaces. It is available in transparent and a variety of colours subject to availability and minimum order. Default colours are red, orange, yellow, blue, black, silver, clear, white and gold. Other custom colours may be available subject to minimum order and lead time.

USES & APPLICATIONS

RS778 is well suited for temporary and permanent applications that require a pressure sensitive tape with excellent adhesion to a wide variety of surfaces and good conformability. Some possible applications include:

- Bundling and wrapping
- Patching and repairs
- Sealing
- Bonding dissimilar materials
- Colour coding and identification

TECHNICAL DATA

Overall Thickness	9.0 mils (0.229mm)
Adhesion to Steel	75 oz./in. (21N/25mm)
Adhesion to Backing	40 oz./in. (11N/25mm)
Tensile Strength	20 lbs./in (88/25mm)

Values listed represent averages of production runs and are not intended to be representative of minimums or maximums

BENEFITS

RS778 is a high performance tough and effective product for use in a variety of temporary and permanent applications

- Aggressive adhesive system bonds and seals on a variety of surfaces
- Conformable backing assists with application to irregular surfaces

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB
T: 020 8295 5440 F: 020 8295 5441
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk